

## Mississippi-R

**T.S.** Total  
Stop


### STANDARD EQUIPMENT

- 3.700.0036 Gun M22 - 3/8"



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0047 Nozzle type 030



- 4.618.0049 High pressure hose 8 m



- Power cable 5 m

### Optional:

- 6.602.0060 ROTOX lance

### Equipped with:

- Three ceramic coated pistons, brass axial pump head with built-in by-pass valve.
- Suction and delivery S. S. valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge.
- Diesel pump with by-pass valve.
- Detergent built-in tank for indirect suction (2,4 lt.)
- Pressure regulator.
- Glycerine pressure gauge.
- Power cable holder.
- Diesel tank capacity 7 lt.
- Ergonomic handle.

|                               | Mississippi-R 1310 XP      |
|-------------------------------|----------------------------|
| code                          | 8.625.0101                 |
| operat. pressure/max          | 130/150 bar-1885/2175 psi  |
| delivery rate                 | 600 l/h-2.64 GPM           |
| abs. power/voltage            | 3000W - 230V~50Hz 1ph      |
| motor/pump type/RPM           | MPBX2/2800 RPM             |
| max. water inlet/outlet temp. | 40/90 °C                   |
| dimension/weight              | 80x55x83cm/60 Kg - 132 lbs |