



## OYSTER

610Z-022 S3 SRC

Standard EN ISO 20345:2011

Size Range 36 - 47



Three-dimensional Spider-net lining: high performance tight-knit three-dimensional structure textile gives an exceptional comfort and keeps the feet dry.



Full grain Idrotech leather with high water repellence properties

Double density polyurethane sole Solid Pu-Pu SRC designed to offer maximum flexibility and lightness.



Maximum lightness and flexibility with Smart Injection, special moulding technology to obtain the Esolight compound, with high abrasion resistance. This process allows to get an exceptionally lighter and thinner outsole, thus giving an excellent flexibility.

The steel toe cap and Inox steel midsole provides protective performance higher than those required by the standard EN 20345.



### Solid · S-01

- Footbed made of PE
- Anatomic for improved comfort.
- Lining with high abrasion resistant

	<b>SRC</b> Slip resistant
	<b>A</b> Antistatic
	<b>P</b> Perforation resistance
	Resistant to 200 joules
	<b>E</b> Energy Absorption of seat region
	<b>FO</b> Fuel oil resistant sole
	<b>WRU</b> Water penetration upper

### Outsole SOLID PU/PU

- SRC Slip resistant outsole.
- FO Fuel resistance.
- Maximum lightness and flexibility thanks to the use of Smart Injection.
- Excellent abrasion resistance.