

SOLAR PANELS

Technical Data Sheet



SYMBOL	pH
T-66	5

Slightly acidic, concentrated product designed for washing and protecting solar panels. Removes exploitative and mineral dirt (soot, dust, grit, water stains). Creates protective hydrophobic coating which slows down renewed dirt settling. Product is biodegradable. 100% sunlight permeability.

APPLICATION:

- solar thermal collectors
- photovoltaic panels

COMPOSITION:

- < 5% non-ionic surfactants
- < 5% cationic surfactants
- auxiliary substances

USAGE:

Thorough cleaning: 1% solution (100 ml / 10 l of water).
Daily cleaning: 0.5% solution (50 ml / 10 l of water).

Apply working solution on solar panel with garden hose and wait 1-2 minutes. Wash it down with high-pressure washer.

Remarks: Use cold or lukewarm water. Using demineralized water eliminates water stains. Do not use this product in full sun.

SOLAR PANELS

Technical Data Sheet

CLASSIFICATION OF THE MIXTURE:



Signal words:
DANGER

Hazard statements:
H318 – Causes serious eye damage.

Precautionary statements:
P310 – Immediately call a POISON CENTER/doctor
P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SELL-BY DATE:

36 months from the production date.
Production date/series and expiration date are stated on the packaging.

ADDITIONAL INFORMATION:

Additional information can be found in safety data sheet.

Contaminated containers should be completely emptied. Several times rinse the container promptly after emptying. Empty container can be stored in containers for collection of plastic packaging, or can be delivered to specialized company for recycling.

Disposal should be in accordance with the national/international regulations